

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 July 2003 (17.07.2003)


PCT

(10) International Publication Number
WO 03/057448 A1


- (51) International Patent Classification⁷: B29C 45/76, 45/28, 45/30 (72) Inventors: DOYLE, Mark; 37 Plummer Avenue, Newburyport, MA 01950 (US). GALATI, Vito; 89 Pleasant Street, Gloucester, MA 01930 (US).
- (21) International Application Number: PCT/US02/41360 (74) Agent: OLIVERIO, Lawrence, M.; Kudirka & Jobse, LLP, One State Street, Suite 1510, Boston, MA 02109 (US).
- (22) International Filing Date: 23 December 2002 (23.12.2002)
- (25) Filing Language: English (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, VN, YU, ZA, ZM, ZW.
- (26) Publication Language: English (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
- (30) Priority Data: 60/342,119 26 December 2001 (26.12.2001) US
- (71) Applicant: SYNVENTIVE MOLDING SOLUTIONS, INC. [US/US]; 10 Centennial Drive, Peabody, MA 01960 (US).

[Continued on next page]


(54) Title: NON-COAXIAL INJECTION MOLDING VALVE FLOW CONTROL



A



B



C

(57) Abstract: In an injection molding machine having upstream (162, 164) and downstream (190, 200) channels communicating with each other for delivering fluid material to one or more mold cavities (170, 180), apparatus for controlling delivery of the melt material from the channels to the one or more mold cavities, each channel having an axis, the downstream channel having an axis (175, 185) intersecting a gate (178, 188) of a cavity of a mold, the upstream channel (162, 164) having an axis (163, 165) not intersecting the gate (178, 188) and being associated with an upstream actuator (30,40) interconnected to an upstream melt flow controller (102, 112) disposed at a selected location within the upstream channel (162, 164), the apparatus comprising a sensor (60, 80, 130) for sensing a selected condition of the melt material at a position downstream of the upstream melt flow controller (102,112); an actuator controller (20) interconnected to the upstream actuator (30, 40), the actuator controller comprising a computer interconnected to a sensor (60, 80, 130) for receiving a signal representative of the selected utilizing a value indicative of the signal received from the sensor as a variable for controlling operation of the upstream actuator, wherein the upstream melt flow controller is adapted to control the rate of flow of the fluid material at the selected location within the upstream channel according to the algorithm.

BEST AVAILABLE COPY

WO 03/057448 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments*

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

NON-COAXIAL INJECTION MOLDING VALVE FLOW CONTROL

RELATED APPLICATIONS

[01] This application claims the benefit of priority under 35 USC Section 119
5 to U.S. provisional patent application serial no. 60/399,409 filed December 26, 2001,
the disclosure of which is incorporated herein by reference in its entirety as if fully set
forth herein.

[02] The disclosures of all of the following are incorporated by reference in
their entirety as if fully set forth herein: U.S. Patent No. 5,894,025, U.S. Patent No.
10 6,062,840, U.S. Patent No. 6,294,122, U.S. Patent No. 6,309,208, U.S. Patent No.
6,287,107, U.S. Patent No. 6,343,921, U.S. Patent No. 6,343,922, U.S. Patent No.
6,254,377, U.S. Patent No. 6,261,075, U.S. Patent No. 6,361,300, U.S. Patent No.
6,464,909, U.S. Patent Application Serial No. 10/214,118, filed August 8, 2002
(7006), U.S. Patent application Serial No. 09/699,856 filed October 30, 2000 (7056),
15 U.S. Patent Application Serial No. 10/269,927 filed October 11, 2002 (7031), U.S.
Application Serial No. 09/503,832 filed February, 15, 2000 (7053), U.S. Application
Serial No. 09/656,846 filed September 7, 2000 (7060), U.S. Application Serial No.
10/006,504 filed December 3, 2001, (7068) and U.S. Application Serial No.
10/101,278 filed March, 19, 2002 (7070).

20

BACKGROUND OF THE INVENTION

[03] Injection molding systems comprise an injection molding machine
having a barrel and a screw (or ram) housed within a barrel which injects a fluid
material from an exit port of the barrel at a preselected velocity or profile of velocities
25 over an injection cycle into a flow channel or system of channels in a distribution
manifold which, in turn, direct the fluid to one or more injection ports which lead to
one or more cavities of one or more molds.

[04] Apparati have been developed for controlling the rate of flow of fluid
material at a location within a flow channel, bore or nozzle having a straight axis that
30 is aligned with the center of the gate of the mold cavity and along which a valve pin
or other mechanical flow controlling mechanism is aligned for purposes of controlling
material flow at the gate or at a position immediately upstream of the gate along the

axis aligned with the gate. Such systems typically use an actuator mechanism that is aligned with the axis that intersects the gate.

SUMMARY OF THE INVENTION

5 **[05]** In accordance with the invention there is provided in an injection molding apparatus having upstream and downstream channels communicating with each other for delivering fluid material to one or more mold cavities, an apparatus for controlling delivery of the melt material from the channels to the one or more mold cavities, each channel having an axis, the downstream channel having an axis
10 intersecting a gate of a cavity of a mold, the upstream channel having an axis not intersecting the gate and being associated with an upstream actuator interconnected to an upstream melt flow controller disposed at a selected location within the upstream channel, the apparatus comprising: a sensor for sensing a selected condition of the melt material at a position downstream of the upstream melt flow
15 controller; an actuator controller interconnected to the upstream actuator, the actuator controller comprising a computer interconnected to a sensor for receiving a signal representative of the selected condition sensed by the sensor, the computer including an algorithm utilizing a value indicative of the signal received from the sensor as a variable for controlling operation of the upstream actuator; wherein the
20 upstream melt flow controller is adapted to control the rate of flow of the fluid material at the selected location within the upstream channel according to the algorithm.

[06] The apparatus can include a downstream melt flow controller movable by a downstream actuator between open flow and closed flow positions within the
25 downstream channel. The downstream actuator is preferably interconnected to the actuator controller, the algorithm utilizing the value indicative of the signal received from the sensor as a variable to control movement of the downstream melt flow controller between the open flow and closed flow positions.

[07] The melt flow controller can be adapted to create a gap of controllably
30 variable size within the upstream channel, the melt flow controller being movable to increase the size of the gap and the rate of flow upon upstream movement of the

melt flow controller. The melt flow controller can be movable to decrease the size of the gap and the rate of flow upon downstream movement of the melt flow controller.

[08] The melt flow controller can comprise a pin having an axis slidably mounted for back and forth movement of the pin through the upstream channel; the pin having a bulbous protrusion along its axis, the bulbous protrusion having a smooth surface extending between an upstream end and a downstream end of the bulbous protrusion and a maximum diameter circumferential surface intermediate the upstream and downstream ends of the bulbous protrusion; the complementary surface of the upstream channel being complementary to the maximum diameter circumferential surface of the bulbous protrusion of the pin; the pin being slidable to a position within the upstream channel such that the maximum diameter circumferential surface of the bulbous protrusion mates with the complementary interior surface portion of the upstream channel. The melt flow controller can comprise a rotary valve.

[09] During an injection cycle having a start point, an end point and an intermediate time duration, the algorithm typically includes a first set of instructions for moving the downstream melt flow controller to the open flow position at the start point and to the closed flow position at the end point and a second set of instructions for moving the upstream controller to a plurality of positions that control the rate of flow of fluid material during the intermediate time duration, the first and second sets of instructions utilizing the value indicative of the signal received from the sensor as a variable for controlling operation of the upstream and downstream actuators.

[10] In another aspect of the invention there is provided, an apparatus for controlling flow of a fluid material in an injection molding apparatus having a flow channel system having an upstream flow channel having a first axis through which fluid material is routed to a downstream channel having a second axis leading to an exit aperture to a mold cavity, the apparatus comprising: a first valve mechanism comprising an actuator drivably interconnected to a fluid material contacting member disposed within the upstream flow channel; the upstream channel communicating with and delivering fluid material to the downstream channel, the downstream channel delivering the fluid material to the exit aperture, the first and second axes of the upstream and downstream channels being non-coaxial; the fluid material

contacting member having an outer surface portion engageable with a complementary surface of a portion of the upstream flow channel to stop flow of the fluid material, the actuator being controllably drivable to drive the outer surface portion of the fluid material contacting member through a selected range of gap distance relative to the complementary surface of the upstream flow channel; the fluid material having a rate of flow through the flow channel system that varies according to the gap distance.

[11] In another aspect of the invention there is provided, an apparatus for controlling flow of a fluid material in an injection molding apparatus having a flow channel system having an upstream flow channel having an axis through which fluid material is routed to a gate of a mold, the apparatus comprising: a first valve mechanism comprising a first actuator drivably interconnected to a fluid material contacting member disposed within the upstream flow channel; the upstream channel communicating with and delivering fluid material to the, the gate of the mold; the axis of the upstream channel being offset from and not intersecting the gate of the mold; the fluid material contacting member having an outer surface portion engageable with a complementary surface of a portion of the upstream flow channel to stop flow of the fluid material, the actuator being controllably drivable to drive the outer surface portion of the fluid material contacting member through a selected range of gap distance relative to the complementary surface of the upstream flow channel; the fluid material having a rate of flow through the flow channel system that varies according to the gap distance.

[12] There is also provided in accordance with the invention a method of controlling fluid flow during an injection cycle in an injection molding machine having a fluid flow distribution system for delivering fluid material to a gate of a mold, the method comprising: injecting fluid through an upstream channel having an axis not intersecting the gate of the mold; regulating the rate of flow of the fluid during the course of the injection cycle at a selected position within the upstream channel according to an algorithm which receives a variable input indicative of a sensed condition of the fluid material sensed by a sensor during the injection cycle; and routing the regulated flow of fluid from the upstream channel to a downstream channel having an axis intersecting the gate of the mold.

[13] In the method, the selected condition of the fluid material can be sensed by the sensor at a position in the flow channel system that is downstream of the selected position in the upstream at which the flow is regulated.

[14] In a preferred embodiment, the method can further comprise regulating the stopping and starting of flow of the fluid material in the injection cycle at a position within the downstream channel. The regulating of the stopping and starting of flow is preferably carried out according to the algorithm based on the variable input indicative of the sensed condition.

BRIEF DESCRIPTION OF THE DRAWINGS

[15] The above and further advantages of the invention may be better understood by referring to the following description in conjunction with the accompanying drawings in which:

[16] Fig. 1 is a partially schematic cross-sectional view of an injection molding system used in one embodiment of the present invention;

[17] Figs. 1A-C are schematic representations of gates to a single mold and to molds of different sizes;

[18] Fig. 2 is an enlarged fragmentary cross-sectional view of the valve pins used as flow contacting and flow rate controlling members in the Fig. 1 system;

[19] Fig. 3 is a partially schematic, plan sectional view of a system according to the invention;

[20] Fig. 4 is a sectional, partially schematic view of the Fig. 3 system;

[21] Fig. 5 is an enlarged fragmentary view of the valve pins used as flow contacting and flow rate controlling members in the Fig. 3 system;

[22] Figs. 6-8 are enlarged, fragmentary views of an alternative valve pin usable as a flow contacting and flow rate controlling member in the Fig. 1 and Fig. 3 systems;

[23] Figs 9-11 are examples of displays that can be displayed on a user interface, the user interface being interconnected to a master computer controller as shown and described with reference to the Figs. 1, 3 embodiments;

[24] Fig. 12 is a side cross-sectional view of a shaftless motor for use as an alternative actuator for flow control mechanism in accordance with the invention, the motor having an axially movable screw for driving the flow controller; and,

[25] Fig. 13 is a schematic side cross-sectional view of a rotary valve flow controller system.

DETAILED DESCRIPTION

[26] FIG 1 shows one embodiment of an injection molding system 10 according to the present invention having a valve gated nozzle 192 and a thermal gated nozzle 202 delivering fluid material to gates 178 and 188 respectively, which in turn communicate with and deliver fluid material to mold cavities 170 and 180 respectively. Fluid material is injected initially under pressure from injection molding machine barrel 120 into a main injection channel 14 formed in heated manifold 12 and travels from channel 14 to common upstream feed channel 160. Channel 160 feeds and communicates with downstream channels 162 and 164 having axes 163, 165 via intermediate upstream channels formed within bushings 108, 118 having axes 104, 114 respectively. The intermediate upstream channels or bores formed within upstream bushings 108, 118 communicate with downstream channels 190, 200 respectively via upstream channels 162, 164 as shown. The downstream channels 190, 200 comprise, in part, bores formed within downstream nozzles/bushings 192, 202 respectively that are disposed at the distal most ends of downstream channels 190, 200. The downstream channels 190, 200 have axes 175, 185 respectively that are aligned with and intersect gates 178, 188 respectively. As shown, the upstream channels 162, 164, the upstream channels formed within bushings 108, 118 and the upstream channel 160 all have axes which are offset from the axes of downstream channels 190, 200 are not coaxial with axes 175, 185 and do not intersect gates 178, 188. Although only two nozzles are shown in FIG. 1, the invention contemplates simultaneously controlling the material flow through a plurality of more than two nozzles to a plurality of gates. In the embodiment shown, the injection molding system 10 is a two mold cavity 170, 180 system. The present invention can be adapted to any of a variety of systems where several downstream channels 183, 185 feed a single uniformly dimensioned cavity 181 in a symmetrical

arrangement, Fig. 1A, or where several channels 193, 195 feed separate cavities 199, 197 of different size/configuration, Fig. 1B, or where several channels 206, 207 feed a single non-uniform cavity 208 at different locations/points of entry where the volumes to be filled 208a, 208b at entry are different, Fig. 1C.

5 **[27]** A system according to the invention is typically used to inject plastic material which is heated/melted to a fluid form and injected through a heated manifold 12 which maintains the plastic material in fluid form. The invention is also applicable to other types of injection systems in which it is useful to control the rate at which another fluid material, e.g., metallic or composite materials is delivered to a
10 cavity of a mold.

[28] The rate at which fluid material is delivered through the channels of the Fig. 1 embodiment is controllably varied by the fluid contacting members 102, 112 which are controllably movable along axes 104, 114 into and out of engagement contact with a complementary mating surface 103, 113, respectively formed within
15 bushings 108, 118. As shown in greater detail in Fig. 2 the fluid contacting member 102 comprises an enlarged bulbous protrusion 102 formed at the distal end of a valve pin 107 which is interconnected at a proximal end to an actuator 40 which is in turn interconnected to a servocontroller 100 which is in turn interconnected to a master controller 20 which typically comprises a computer or other digital data
20 processing mechanism containing a program that executes one or more algorithms that use one or more variables indicative of a signal received from one or more sensors 60, 80, 130 that sense a selected condition of the fluid material flowing through the various channels or bores of the system 10. As shown in the Fig. 1 embodiment, actuator 40, pin 107 and member 102 control fluid flow from common
25 upstream channel 160 to a valve gated downstream channel 190 while a actuator 30, pin 117, member 112, servomechanism 110 control flow to a thermal gated channel 200.

[29] The master computer or controller 20 receives signal inputs indicative of a fluid material condition from three sensors 60, 80 and 130 in the Fig. 1 system.
30 All of the sensors as shown in Fig. 1 sense a condition of the fluid at a location or position that are downstream of the location at which fluid rate controlling members 102, 112 are positioned. In a preferred embodiment, the algorithm of the computer

20 includes instructions for controlling the movement of actuator 40 and pin 102 to control the rate of fluid flow during an injection cycle through a gap 102g, Fig. 2 that is controllably variable in size via controlled movement of pin 107 along axis 104. The algorithm also includes instruction for controlling the opening and closing of gate 178 during the same injection cycle via controlled movement of pin 195 along axis 175 between gate open and gate closed positions. Pin 195 closes gate 178 off by engagement of the distal end of pin 195 with a complementary receiving aperture at the end of nozzle 192 that communicates with mold cavity 170.

[30] As shown in Fig. 2, the fluid contacting member 102 has a surface 102s which is complementary to a mating surface 103 within the flow channel. When the two surfaces mate, i.e. when the member 102 is in the position 102p in dashed lines in Fig. 2, flow is stopped. Between the 102p position and the solid line 102 position shown in Fig. 2, the gap 102g varies in size and the rate of fluid flow varies depending on the size of the gap. In the Fig. 1, 2 embodiment, the fluid flow rate decreases on forward upstream movement 107u of the valve pin 107 and actuator 40. Conversely, fluid flow rate increases on backward downstream movement 107d of pin 107. Pin 117, member 112, surface 113 and actuator 30 function in the same manner as their analogous components described above on upstream 117u and downstream 117d movement of pin 117, member 112 and actuator 30.

[31] Upstream movement of a fluid contacting member, pin or the like means that the member moves against/in the opposite direction of the flow of the fluid. Downstream movement means that the member moves in the same direction as the flow of fluid. Upstream movement to decrease and/or stop flow rate is preferred, at least when using the pin embodiments of Figs. 1-5.

[32] Fig. 3 shows an embodiment with two upstream channels within bushings 108a, 118a having control pins 107a and 117a respectively. Each of valve pins 108a and 118a separately controls fluid flow rate to a pair of downstream channels and gates (one downstream gate and nozzle shown, 200c, Fig. 4). Each of the downstream gates is controlled by a valve similar to the valve arrangement shown in Fig. 4 for controlling the start and flow stop points of an injection cycle. As shown in Fig. 3 each gate is associated with an actuator 50a, 50b, 50c, 50d which is

interconnected to a valve pin such as pin 200a, Fig. 4, which opens and closes a gate, e.g. gate 200c leading to a mold cavity.

[33] Valve pins 107a, 117a are mechanically interconnected to respective hydraulic actuators 40a, 30a which are in turn interconnected to servomechanisms 100a which are in turn controlled by computer 20a. Computer 20a includes an algorithm which utilizes a value indicative of a signal received from downstream sensors 60a, 80a which sense a selected condition of the fluid material at a position downstream of the location of the point of fluid flow rate control, i.e. surfaces 103a, 113a within bushings 108a, 118a. The algorithm controls the operation of actuators 40a, 30a which in turn control axial movement of pins 107a, 117a and their associated enlarged fluid contacting members 102a, 112a within the bores of bushings 108a, 118a. Fig. 5 shows in greater detail a configuration of a fluid contacting member 102a.

[34] As shown in Fig. 5, pin 107a is movable in an upstream direction 107u and downstream direction 107d along axis 104a. The upstream movement of pin 107a is accomplished by backward movement of actuator 40a as opposed to forward movement of actuators 40, 30 in the Fig. 1 embodiment. A contoured surface 102o of pin protrusion 102a is configured to be complementary with channel surface 103a such that surfaces 102o and 103a may mate upon complete upstream withdrawal of pin 107a whereby flow is stopped. As shown a gap 103c between surfaces 102o and 103a can be controllably varied in size depending on the position of pin 107a along axis 104a. Upstream movement, 107u, 117u of pins 107a and 117a causes a gap such as gap 103c to decrease in size and thus decrease the rate of fluid flow 109a from common upstream channel 160a to channels 162a, 167. Conversely, downstream movement 107d, 117d of pins 102a, 112a causes the gap, e.g. gap 103c, to increase in size and thus increase fluid flow rate. As shown, main barrel channel 120 feeds upstream channel 160a which commonly feeds the bores or channels within bushings 108a, 118a. The flow from bushings 108a, 118a feeds intermediate downstream channels 162a, 164a which feed intermediate channels 167, 169. Intermediate downstream channels 167, 169 commonly feed the bores/channels associated with actuators 50a-d, e.g. bore 200a, Fig. 4, all of which have an axis, e.g. 200x, which intersect and lead to gates, e.g. gate 200c, and their

associated mold cavities. As shown in Fig. 4, common feed channel 169 communicates with a lateral channel 177 provided in bushing 202a which communicates with the bore/channel 200a within bushing 202a.

[35] In both of the embodiments of Figs. 1, 2 and Figs. 3-5, the rate of flow is decreased by upstream movement of the fluid contacting member and increased by downstream movement. As shown, the position at which fluid flow rate is controlled is located within a channel, having an axis, e.g. 104a, 114a, Fig. 4, which is not coaxial with the downstream channels having an axis that intersects a gate leading to a mold, e.g. channel 200a having axis 200x intersecting gate 200c, Fig. 4.

[36] Figs. 6-8 show an alternative melt flow controller embodiment for use in the invention. As shown, pin 107t is slidably mounted in a mounting channel 108m having a diameter equal to the maximum diameter of midsection, 102m of the fluid contacting member 102t such that the pin 107t can be entirely withdrawn in the direction 107u from the manifold and bushing 108t and readily replaced without disassembling any portion of the manifold or bushing 108t. The maximum diameter midsection 102m has the same diameter as the complementary flow restricting throat surface 103s of the bushing 108t such that when the two surfaces mate flow is stopped. As shown in Figs. 7 and 8, the rate of flow and the size of the flow rate determining gap 103g can be controllably varied by either upstream movement 107u, Fig. 8 or downstream movement, 107d, Fig. 7 of pin 107t. Upstream movement 107u can form gap 103g between bushing surface 108g, Fig. 8, and the lower outer surface of member 102t. Downstream movement 107d, Fig. 7, can also form a gap 103g between channel surfaces 103s, 108g and the upper portion of the outer surface of member 102t. As described above, controlled movement of pin 107t by computer 20 controls the size of the gap 103g and thus the rate of flow from upstream channel 160 to downstream channel 162t which leads to downstream channel 190 or 200 or the like. Axis x as shown in Figs. 6-8 corresponds to axis 104 of Fig. 1 and is not coaxial with axis 175 of the downstream bore 190 leading to a gate such as 175.

[37] In the embodiments shown, a pressure sensor is typically used to sense the pressure of the fluid material in the channel locations shown downstream of the upstream flow control members. In operation, the conditions sensed by the

pressure transducer associated with each channel are fed back to a control system that typically includes PID algorithmic controllers (proportional, integral, derivative). The computer 20 typically executes a proportional, integral, derivative algorithm which compares the sensed pressure (at a given time) from the pressure transducer to a programmed target pressure (for the given time). The computer 20 instructs the PID controller to adjust the position of the flow controller or valve pin using the actuators in order to mirror the target pressure for that given time. In this way a programmed target pressure or profile of pressure versus time (described in detail below) for an injection cycle for a particular part for each downstream channel or gate can be followed by the computer or controller 20.

[38] As to each separate downstream channel leading to a gate, the target pressure or pressure profile may be different, particularly where the channels are injecting into separate cavities, and thus separate algorithms or programs for achieving the target pressures at each nozzle may be employed. As can be readily imagined, a single computer or CPU may be used to execute multiple programs/algorithms for each channel leading to a gate or separate computers may be utilized.

[39] Other sensed conditions can be used which relate to melt flow rate other than pressure. For example, the position of a melt flow controller or valve pin or the load on the valve pin could be the sensed condition. If so, a position sensor or load sensor, respectively, could be used to feed back the sensed condition to the PID controller.

[40] The embodiments described control the rate of melt flow away from the gate along a channel axis offset from a channel having an axis intersecting and leading to a gate thus enabling control of flow rate to multiple channels intersecting multiple gates. Controlling the melt flow away from the gate also enables a pressure or other material condition sensor to be located away from a gate.

[41] In practical operation, a target profile of the condition of the fluid material over the period of time of an injection cycle is created for each downstream channel where a sensor is located. To create a target profile for a particular and the mold cavity associated therewith, the injection molding machine is first set at maximum injection pressure and screw speed, and parameters relating to the

injection pressure, injection time, pack and hold pressure and pack and hold time are set on the computer 20 at values that the molder estimates will generate good parts based on part size, shape, material being used, experience, etc. Trial and error Injection cycles are run for the selected channels and their associated, e.g. for channels 190, 200 and their associated mold cavities 170, 180, with alterations being made to the above parameters depending on the condition of the parts to be produced. When the most satisfactory parts are produced during a trial injection cycle run, the profile of fluid material condition that produced the most satisfactory parts is determined for those particular channels or nozzle bores and the cavities associated therewith. This process is repeated for all channels in which a sensor is mounted until target fluid condition profiles are ascertained for each channel having a sensor and cavity associated therewith. Preferably, the predetermined ideal target profiles are stored in computer 20 and used by the computer for controlling servomechanisms 100, 110 and 115 during actual production injection cycles.

[42] The foregoing process of ideal profile creation can be used with any number of channels having a sensor. Although it may be preferable to profile one channel and associated cavity at a time (while the other channels are closed) in a "family tool" mold application, the target profiles can also be created by running all channels simultaneously, and similarly adjusting each channel profile according to the quality of the parts produced. This would be preferable in an application where all the channels are injecting into like cavities, since the profiles should be similar, if not the same, for each channel and its associated cavity.

[43] In single cavity applications (where multiple channels from a manifold are injecting into a single cavity), the target profiles can also be created by running the channels at the same time and adjusting the profiles for each channel according to the quality of the part being produced.

[44] The system can be implemented using a user interface 214, Figs. 9a-b in which each target profile can be stored, displayed and sent as an input to the algorithm to be executed by the computer/controller 20. Alternatively the profile data can be input to and stored directly in the computer without the interface.

[45] Figs. 9a-b show one example of pressure versus injection cycle time graphs (235, 237) of the pressure detected by the two pressure transducers 60a,

80a associated with the two channels 167, 169. The graphs of Figs. 9a-b are generated and/or displayed on the user interface 214 so that a user can observe the tracking of the actual pressure during an actual injection cycle versus the target pressure during the course of an actual injection cycle in real time, or after the cycle is complete. The two different graphs of Figs. 9a and 9b show two independent target pressure profiles ("desired") emulated by the two channels 167, 169. Different target profiles may be desirable to uniformly fill different sized mold cavities associated with each channel that is associated with actuators 50a-d, or to uniformly fill different sized sections of a single cavity. Profiles such as these can be generated with respect to any embodiments of the invention.

[46] The melt flow controller, 102a associated with graph 235 is opened sequentially at. 5 seconds after the melt flow controller 112a associated with graph 237 is opened at. 00 seconds. During injection (for example,. 00 to 1.0 seconds in Fig. 9b) and pack and hold (for example, 1.0 to 6. 25 seconds in Fig. 9b) portions of the graphs, each melt flow controller 102a, 112a (or fluid contacting member) is controllably moved to a plurality of positions to alter the pressure sensed by the pressure transducers 60a, 80a to track the target pressure profiles.

[47] Through the user interface 214, target profiles can be designed, and changes can be made to any target profile using standard windows-based editing techniques.

[48] The profiles are then used by computer 20 to control the actuators 50a-d and thus control the position of the valve pins 107a and 117a. For example, Fig. 10 shows an example of a profile creation and editing screen icon 300 generated on interface 214.

[49] Screen icon 300 is generated by a windows-based application performed on interface 214. Alternatively, this icon could be generated on an interface associated with controller 20. Screen icon 300 provides a user with the ability to create a new target profile or edit an existing target profile for any given nozzle and cavity associated therewith.

[50] A profile 310, Fig. 10, includes (x, y) data pairs, corresponding to time values 320 and pressure values 330 which represent the desired pressure sensed by the pressure transducer for the channel being profiled. The screen icon shown in

Figure 10 is shown in a "basic" mode in which a limited group of parameters are entered to generate a profile. For example, in the foregoing embodiment, the "basic" mode permits a user to input start time displayed at 340, maximum fill pressure displayed at 350 (also known as injection pressure), the start of pack time displayed at 360, the pack and hold pressure displayed at 370, and the total cycle time displayed at 380.

[51] The screen also allows the user to select the particular melt flow controller they are controlling displayed at 390, and name the part being molded displayed at 400. Each of these parameters can be adjusted independently using standard windows-based editing techniques such as using a cursor to actuate up/down arrows 410.

[52] By clicking on a pull-down menu arrow 391, the user can select different channel melt flow controllers in order to create, view or edit a profile for the selected channel and cavities associated therewith. Also, a part name 400 can be entered and displayed for each selected channel flow controller.

[53] The newly edited profile can be saved in computer memory individually, or saved as a group of profiles for a group of channels that inject into a particular single or multicavity mold. The term "recipe" is used to describe a group of profiles for a particular mold and the name of the particular recipe is displayed at 430 on the screen icon.

[54] To create a new profile or edit an existing profile, first the user selects a particular channel for the particular recipe being profiled. The flow controller selection is displayed at 390. The user inputs an alpha/numeric name to be associated with the profile being created, for family tool molds this may be called a part name displayed at 400. The user then inputs a time displayed at 340 to specify when injection starts. A delay can be with particular channel controllers to sequence the opening of the valves and the injection of melt material into different gates of a mold.

[55] The user then inputs the fill (injection) pressure displayed at 350. In the basic mode, the ramp from zero pressure to max fill pressure is a fixed time, for example, 3 seconds. The user next inputs the start pack time to indicate when the pack and hold phase of the injection cycle starts. The ramp from the filling phase to

the packing phase is also fixed time in the basic mode, for example, at about 0.3 seconds.

[56] The final parameter is the cycle time which is displayed at 380 in which the user specifies when the pack and hold phase (and the injection cycle) ends. The ramp from the pack and hold phase to zero pressure at about 16.5 seconds will be instantaneous when a valve pin (e.g. 195) as in the Figs. 1-5 embodiments is used to close a gate, or slower in a thermal gate (e.g. Fig. 1, nozzle 202) due to the residual pressure in the cavity which will decay to zero pressure once the part solidifies in the mold cavity. The "cool" time typically begins upon the drop to zero pressure and lasts to the end of the cycle, e.g. 16.5-30.0 seconds in Fig. 10.

[57] User input buttons 415 through 455 are used to save and load target profiles.

[58] Button 415 permits the user to close the screen. When this button is clicked, the current group of profiles will take effect for the recipe being profiled. Cancel button 425 is used to ignore current profile changes and revert back to the original profiles and close the screen. Read Trace button 435 is used to load an existing and saved target profile from memory. The profiles can be stored in memory contained in the interface 215 or the controller 210. Save trace button 440 is used to save the current profile. Read group button 445 is used to load an existing recipe group. Save group button 450 is used to save the current group of target profiles for a group of flow controllers. The process tuning button 455 allows the user to change the PID settings (for example, the gains) for a particular channel valve in a control zone. Also displayed is a pressure range 465 for the injection molding application.

[59] Button 460 permits the user to toggle to an "advanced" mode profile creation and editing screen. The advanced profile creation and editing screen is shown in Figure 11.

[60] The advanced mode allows a greater number of profile points to be inserted, edited, or deleted than the basic mode. As in the basic mode, as the profile is changed, the resulting profile is displayed.

[61] The advanced mode offers greater profilability because the user can select values for individual time and pressure data pairs. As shown in the graph 420, the profile 470 displayed is not limited to a single pressure for fill and pack/hold,

respectively, as in the basic mode. In the advanced mode, individual (x, y) data pairs (time and pressure) can be selected anywhere during the injection cycle.

5 **[62]** To create and edit a profile using advanced mode, the user can select a plurality of times during the injection cycle (for example 16 different times), and select a pressure value for each selected time. Using standard windows-based editing techniques (arrows 475) the user assigns consecutive points along the profile (displayed at 478), particular time values displayed at 480 and particular pressure values displayed at 485.

10 **[63]** The next button 490 is used to select the next point on the profile for editing. Prev button 495 is used to select the previous point on the profile for editing. Delete button 500 is used for deleting the currently selected point. When the delete button is used the two adjacent points will be redrawn showing one straight line segment.

15 **[64]** The add button 510 is used to add a new point after the currently selected point in which time and pressure values are entered for the new point. When the add button is used the two adjacent points will be redrawn showing two segments connecting to the new point.

20 **[65]** Sensors which detect properties other than pressure may be employed. Preferably, sensors are used which detect a property of the fluid or of the operation of the mechanisms that control fluid flow rate. Data indicative of flow rate typically comprises a fluid property that is readily correlatable to or convertible by an algorithm to the time or rate of filling of the mold cavity. Fluid pressure leading to or through an injection port is one example of flow rate data. The position of a mechanical flow controller mechanism such as a valve pin, rotary valve, plunger or
25 ram; the position of an actuator that can be used to control movement of a pin, rotary valve, plunger or ram; the force or pressure exerted by an actuating mechanism (e.g. hydraulic, pneumatic actuator), electric motor, ram or the like; the electrical power or hydraulic or pneumatic pressure that is used to drive an actuating mechanism, motor, ram or the like during an injection cycle are other examples of data that a
30 sensor can record and be converted to a variable for input to an algorithm executable by a computer 20, 20a for controlling the movement of a melt flow controller or fluid contacting member.

[66] Following is a list of exemplary flow rate indicative parameters that a sensor can be used to detect for use in the invention:

- position of a flow controlling valve pin or actuator cylinder;
- force or pressure exerted on or by a flow controlling valve pin, actuator
5 cylinder, ram, screw or motor;
- energy or power used to operate a flow controlling actuator, ram, motor or the like;
- flow rate recorded by a mechanical, optical or electronic sensing flowmeter;
- 10 - flow volume injected over time by a machine ram/screw;
- velocity of movement of a flow controlling component such as valve pin, alternative ram, plunger, rotary valve or the like.

[67] As described with respect to the Figs. 9-11 profile of fluid pressure data, a similar profile of data for any of the above variables over the time of an
15 injection cycle may be obtained by trial and error running of an injection molding apparatus and then used as a target profile to be emulated by an algorithm to control the movement of a melt flow controller during an injection cycle.

[68] Fig. 12 shows an example of an electrically powered motor which may be used as an actuator 301, in place of a fluid driven mechanism (such as 30, 40, 30a, 40a, Figs. 1, 3) for driving a valve pin or rotary valve or other nozzle flow control
20 mechanism. In the embodiment shown in Fig. 12 a shaftless motor 300a mounted in housing 302 has a center ball nut 304 in which a screw 306 is screwably received for controlled reciprocal driving 308 of the screw 308a along axis XX. Other motors which have a fixed shaft in place of the screw may also be employed as described
25 more fully in US application serial no. 09/187,974, the disclosure of which is incorporated herein by reference. As shown in the Fig. 12 embodiment the nut 304 is rigidly interconnected to magnet 310c and mounting components 310a, 310b which are in turn fixedly mounted on the inner race of upper rotational bearing 312 and lower rotational bearing 314 for rotation of the nut 304 relative to housing 302 which

is fixedly interconnected to the manifold 15a of the injection molding machine. The axially driven screw 308a is fixedly interconnected to valve pin 41 which reciprocates 308 along axis X together with screw 308a as it is driven. As described more fully below, pin 41 is preferably readily detachably interconnected to the moving
5 component of the particular actuator being used, in this case screw 308a. In the Fig. 22 embodiment, the head 41a of pin 41p is slidably received within a complementary lateral slot 321 provided in interconnecting component 320a. The housing 302 may be readily detached from manifold 15a by unscrewing bolts 324 and lifting the housing 302 and sliding the pin head 41a out of slot 321 thus making the pin readily
10 accessible for replacement.

[69] As can be readily imagined other motors may be employed which are suitable for the particular flow control mechanism which is disposed in the flow channel of the manifold or nozzle, e.g. valve pin or rotary valve. For example, motors such as a motor having an axially fixed shaft having a threaded end which
15 rotates together with the other rotating components of the actuator 301 and is screwably received in a complementary threaded nut bore in pin interconnecting component 320, or a motor having an axially fixed shaft which is otherwise screwably interconnected to the valve pin or rotary valve may be employed.

[70] Controlled rotation 318 of screw 308a, Fig 22, is achieved by
20 interconnection of the motor 300a to a motor controller 316 which is in turn interconnected to the CPU, the algorithm of which (including PID controllers) controls the on/off input of electrical energy to the motor 300a, in addition to the direction and speed of rotation 318 and the timing of all of the foregoing. Motor controller 316 may comprise any conventional motor control mechanism(s) which are suitable for the
25 particular motor selected. Typical motor controllers include an interface 316a for processing/interpreting signals received from the computer 20 similar to the interface 214 described with reference to Figs 9-11; and, the motor controllers typically comprise a voltage, current, power or other regulator receiving the processed/interpreted signals from interface 316a that regulates the speed of
30 rotation of the motor 300 according to the instruction signals received from computer 20.

[71] Fig. 13 shows a pair of rotary valve flow controllers 200' mounted in a heated manifold 15' for distribution of fluid material from a main barrel injection channel 13' to a common upstream distribution channel 13d having an axis Z to downstream channels 20d having an axis X' that intersects the gates 9a of mold cavity 9i. As shown in Fig. 13, the axis Z of upstream channel 13d is not coaxial with the axis X' of downstream channels 20d. The rotary valves 200' are disposed within the off axis channel 13d for controlling flow rate based on variables indicative of sensor signals sent by downstream sensors 60t, 80t and received in some form by master computer controller 20 for use in a control algorithm. As shown in schematic form in Fig. 13, the rotary valves comprise a housing 206' in which a plug 202' is rotatably mounted. The plug has a central flow channel or bore 204' which is rotatably alignable with feed bores 201' provided within the body of housing 206'. Depending on the degree of rotational alignment of plugs 202' and channels 204' with housing bores 201', fluid will flow at a variable rate from channel 13d through channels 204' into non-coaxial downstream channels/bores 20d which lead to gates 9a. Plugs 202' are rotatable to a selected degree by drive mechanisms or actuators 110', 115'. Typically actuators 110', 115' comprise electric motors or electrically powered actuators but can comprise any suitable actuator for effecting rotation of plugs 202'. The actuators 110', 115' are interconnected to and receive command signals from computer controller 20 which contains a control algorithm as described above for controlling the degree of rotation of plugs 202' and thus the rate of fluid flow during an injection cycle in the same manner as described with reference to the Figs. 1-12 embodiments. As shown in Fig. 13, bore 204' is in a fully aligned, full open flow rotational position with respect to downstream channel 20d wherein bore 204', actuator 115' and 208' are at an intermediate point in an injection cycle which is in operating to regulate fluid flow; and, as shown in Fig. 13, bore 204'' is in a fully not aligned, flow stop rotational position with respect to downstream channel 20d wherein bore 204'', actuator 110' and 208'' are at either a cycle end/stop or cycle point in an injection cycle where flow is stopped.

[72] Sensors 60t and 80t are mounted downstream of the rotary valves 200' and provide the fluid material condition data as variable inputs to the algorithm of computer 20 in the same manner as described above to control the operation of

actuators 110', 115' during an injection cycle. As shown in Fig. 13, downstream channels 20d include actuators 208' and valve pins 41', 41". Valve pins 41', 41" are interconnected to actuators 208' for reciprocal movement along axes X' between open flow and closed flow positions wherein the distal ends of the valve pins 41', 41" close off the downstream channels 20d at gate 9a when moved to their fully downstream direction by actuators 208' at the end of an injection cycle. As shown in Fig. 13, valve pin 41" is in a fully downstream gate closed position and valve pin 41' is in its upstream open flow position. The operation of downstream actuators 208' is similarly controlled by the algorithm of computer 20 based on the sensor 60t, 80t signal data that is sent to computer and used by the algorithm as a variable input. As with the embodiments described above, the downstream actuators 208' provide the function of opening and closing the gates at the beginning and end of an injection cycle while the upstream rotary valves 200' provide the function of controlling the rate of fluid flow during the injection cycle between start and stop. As described above with reference to Figs. 9-11, a flow rate profile can be predetermined and stored and the operation of rotary valves 200' can then be controlled by computer 20 to emulate the predetermined flow rate profile that is stored in computer 20 or other memory communicating with the algorithm of computer 20.

[73] What is claimed is:

CLAIMS

1 1. In an injection molding apparatus having upstream and downstream channels
2 communicating with each other for delivering fluid material to one or more mold
3 cavities, apparatus for controlling delivery of the melt material from the channels to
4 the one or more mold cavities, each channel having an axis, the downstream
5 channel having an axis intersecting a gate of a cavity of a mold, the upstream
6 channel having an axis not intersecting the gate and being associated with an
7 upstream actuator interconnected to an upstream melt flow controller disposed at a
8 selected location within the upstream channel, the apparatus comprising:

9 A sensor for sensing a selected condition of the melt material at a position
10 downstream of the upstream melt flow controller;

11 An actuator controller interconnected to the upstream actuator, the actuator
12 controller comprising a computer interconnected to a sensor for receiving a signal
13 representative of the selected condition sensed by the sensor, the computer
14 including an algorithm utilizing a value indicative of the signal received from the
15 sensor as a variable for controlling operation of the upstream actuator;

16 Wherein the upstream melt flow controller is adapted to control the rate of flow
17 of the fluid material at the selected location within the upstream channel according to
18 the algorithm.

1 2. Apparatus of claim 1 further comprising a downstream melt flow
2 controller movable by a downstream actuator between open flow and closed flow
3 positions within the downstream channel.

1 3. Apparatus of claim 2 wherein the downstream actuator is interconnected to
2 the actuator controller, the algorithm utilizing the value indicative of the signal
3 received from the sensor as a variable to control movement of the downstream melt
4 flow controller between the open flow and closed flow positions.

1 4. Apparatus of claim 1 wherein the melt flow controller is adapted to create a
2 gap of controllably variable size within the upstream channel, the melt flow controller
3 being movable to increase the size of the gap and the rate of flow upon upstream
4 movement of the melt flow controller.

1 5. Apparatus of claim 1 wherein the melt flow controller is adapted to create a
2 gap of controllably variable size within the upstream channel, the melt flow controller
3 being movable to decrease the size of the gap and the rate of flow upon downstream
4 movement of the melt flow controller.

1 6. Apparatus of claim 1 wherein the melt flow controller comprises a pin having
2 an axis slidably mounted for back and forth movement of the pin through the
3 upstream channel;
4 the pin having a bulbous protrusion along its axis, the bulbous protrusion having a
5 smooth surface extending between an upstream end and a downstream end of the
6 bulbous protrusion and a maximum diameter circumferential surface intermediate the
7 upstream and downstream ends of the bulbous protrusion;
8 the complementary surface of the upstream channel being complementary to the
9 maximum diameter circumferential surface of the bulbous protrusion of the pin;

10 the pin being slidable to a position within the upstream channel such that the
11 maximum diameter circumferential surface of the bulbous protrusion mates with the
12 complementary interior surface portion of the upstream channel.

1 7. Apparatus of claim 1 wherein the melt flow controller comprises a rotary valve.

1 8. Apparatus of claim 1 wherein the actuator comprises a mechanically movable
2 member interconnected to the melt flow controller, the mechanically movable
3 member being controllably drivable for movement through a predetermined path of
4 travel according to the algorithm.

1 9. Apparatus of claim 8 wherein the mechanically movable member is drivable
2 by hydraulic, pneumatic or electrical energy, force or power.

1 10. Apparatus of claim 2 wherein, during an injection cycle having a start point, an
2 end point and an intermediate time duration, the algorithm includes a first set of
3 instructions for moving the downstream melt flow controller to the open flow position
4 at the start point and to the closed flow position at the end point and a second set of
5 instructions for moving the upstream controller to a plurality of positions that control
6 the rate of flow of fluid material during the intermediate time duration, the first and
7 second sets of instructions utilizing the value indicative of the signal received from
8 the sensor as a variable for controlling operation of the upstream and downstream
9 actuators.

1 11. Apparatus for controlling flow of a fluid material in an injection molding
2 apparatus having a flow channel system having an upstream flow channel having a
3 first axis through which fluid material is routed to a downstream channel having a
4 second axis leading to an exit aperture to a mold cavity, the apparatus comprising:
5 a first valve mechanism comprising an actuator drivably interconnected to a
6 fluid material contacting member disposed within the upstream flow channel;
7 the upstream channel communicating with and delivering fluid material to the
8 downstream channel, the downstream channel delivering the fluid material to the exit
9 aperture, the first and second axes of the upstream and downstream channels being
10 non-coaxial;
11 the fluid material contacting member having an outer surface portion
12 engageable with a complementary surface of a portion of the upstream flow channel
13 to stop flow of the fluid material, the actuator being controllably drivable to drive the
14 outer surface portion of the fluid material contacting member through a selected
15 range of gap distance relative to the complementary surface of the upstream flow
16 channel;
17 the fluid material having a rate of flow through the flow channel system that
18 varies according to the gap distance.

1 12. The apparatus of claim 11 further comprising a controller interconnected to
2 the actuator, the controller including an algorithm that controls movement of the
3 actuator according to a variable defined by a signal received by the controller from a
4 sensor that senses a selected condition of the fluid material flowing through the flow
5 channel system.

1 13. The apparatus of claim 11 wherein the outer surface of the fluid contacting
2 member engages with the complementary surface of the upstream channel upon
3 upstream movement of the fluid contacting member.

1 14. The apparatus of claim 11 wherein the outer surface of the fluid contacting
2 member engages with the complementary surface of the upstream channel upon
3 downstream movement of the fluid contacting member.

1 15. The apparatus of claim 11 wherein the fluid contacting member comprises a
2 pin having an axis slidably mounted for back and forth movement of the pin through
3 the upstream channel;
4 the pin having a bulbous protrusion along its axis, the bulbous protrusion having a
5 smooth surface extending between an upstream end and a downstream end of the
6 bulbous protrusion and a maximum diameter circumferential surface intermediate the
7 upstream and downstream ends of the bulbous protrusion;
8 the complementary surface of the upstream channel being complementary to the
9 maximum diameter circumferential surface of the bulbous protrusion of the pin;
10 the pin being slidable to a position within the channel such that the maximum
11 diameter circumferential surface of the bulbous protrusion mates with the
12 complementary interior surface portion of the channel.

1 16. The apparatus of claim 11 wherein the sensor is mounted for sensing the
2 selected condition of the fluid material at a position upstream of the complementary
3 surface of the upstream channel.

1 17. The apparatus of claim 11 wherein the sensor is mounted for sensing the
2 selected condition of the fluid material at a position downstream of the
3 complementary surface of the upstream channel.

1 18. The apparatus of claim 11 further comprising a second valve mechanism
2 comprising a second actuator drivably interconnected to a second fluid material
3 contacting member disposed within the downstream flow channel;
4 the second fluid material contacting member having an outer surface portion
5 engageable with a complementary surface of a portion of the downstream flow
6 channel to stop flow of the fluid material;
7 the second actuator being controllably drivable to drive the outer surface
8 portion of the second fluid material contacting member between an open flow
9 position and a closed flow position.

1 19. The apparatus of claim 18 wherein the second valve mechanism is
2 interconnected to the flow controller, the algorithm including a set of instructions for
3 controlling the drive of the second valve mechanism.

1 20. Apparatus for controlling flow of a fluid material in an injection molding
2 apparatus having a flow channel system having an upstream flow channel having an

3 axis through which fluid material is routed to a gate of a mold, the apparatus
4 comprising:
5 a first valve mechanism comprising a first actuator drivably interconnected to
6 a fluid material contacting member disposed within the upstream flow channel;
7 the upstream channel communicating with and delivering fluid material to the,
8 the gate of the mold;
9 the axis of the upstream channel being offset from and not intersecting the
10 gate of the mold;
11 the fluid material contacting member having an outer surface portion
12 engageable with a complementary surface of a portion of the upstream flow channel
13 to stop flow of the fluid material, the actuator being controllably drivable to drive the
14 outer surface portion of the fluid material contacting member through a selected
15 range of gap distance relative to the complementary surface of the upstream flow
16 channel;
17 the fluid material having a rate of flow through the flow channel system that
18 varies according to the gap distance.

1 21. The apparatus of claim 20 further comprising a downstream channel
2 communicating with the upstream channel, the downstream channel having an axis
3 intersecting the gate of the mold.

1 22. The apparatus of claim 20 wherein the gap distance is increased on
2 movement of the flow contacting member in an upstream direction away from the
3 complementary surface of the upstream flow channel.

1 23. The apparatus of claim 20 wherein the gap distance is increased on
2 movement of the flow contacting member in a downstream direction away from the
3 complementary surface of the upstream flow channel.

1 24. The apparatus of claim 20 wherein the fluid contacting member comprises a
2 pin having an axis slidably mounted for back and forth movement of the pin through
3 the upstream channel;
4 the pin having a bulbous protrusion along its axis, the bulbous protrusion having a
5 smooth surface extending between an upstream end and a downstream end of the
6 bulbous protrusion and a maximum diameter circumferential surface intermediate the
7 upstream and downstream ends of the bulbous protrusion;
8 the complementary surface of the upstream channel being complementary to the
9 maximum diameter circumferential surface of the bulbous protrusion of the pin;
10 the pin being slidable to a position within the channel such that the maximum
11 diameter circumferential surface of the bulbous protrusion mates with the
12 complementary interior surface portion of the channel.

1 25. The apparatus of claim 20 further comprising a second valve mechanism
2 comprising a second actuator drivably interconnected to a second fluid material
3 contacting member disposed within the downstream flow channel;
4 the second fluid material contacting member having an outer surface portion
5 engageable with a complementary surface of a portion of the downstream flow
6 channel to stop flow of the fluid material;

7 the second actuator being controllably drivable to drive the outer surface
8 portion of the second fluid material contacting member between an open flow
9 position and a closed flow position.

1 26. The apparatus of claim 25 wherein the first and second valve mechanisms are
2 interconnected to a flow controller having an algorithm that includes a set of
3 instructions for controlling the drive of the first and second valve mechanisms.

1 27. The apparatus of claim 26 further comprising a sensor for sensing a selected
2 condition of the fluid material and sending a signal indicative of the sensed condition
3 to the flow controller, the algorithm utilizing a value corresponding to the signal as a
4 variable to control the drive of the first and second valve mechanisms.

1 28. Method of controlling fluid flow during an injection cycle in an injection molding
2 machine having a fluid flow distribution system for delivering fluid material to a gate
3 of a mold, the method comprising:

4 injecting fluid through an upstream channel having an axis not intersecting the
5 gate of the mold;

6 regulating the rate of flow of the fluid during the course of the injection cycle at a
7 selected position within the upstream channel according to an algorithm which
8 receives a variable input indicative of a sensed condition of the fluid material sensed
9 by a sensor during the injection cycle;

10 routing the regulated flow of fluid from the upstream channel to a downstream
11 channel having an axis intersecting the gate of the mold.

1 29. The method of claim 28 wherein the selected condition of the fluid material is
2 sensed by the sensor at a position in the flow channel system that is downstream of
3 the selected position in the upstream at which the flow is regulated.

1 30. The method of claim 28 further comprising regulating the stopping and
2 starting of flow of the fluid material in the injection cycle at a position within the
3 downstream channel.

1 31. The method of claim 30 wherein the regulating of the stopping and starting of
2 flow is carried out according to the algorithm based on the variable input indicative of
3 the sensed condition.




Fig. 1

2/13




Fig. 1A




Fig. 1B




Fig. 1C

3/13




Fig. 2




Fig. 3

5/13




Fig. 4

6/13






Fig. 5

**Fig. 6****Fig. 7**

8/13




Fig. 8

9/13




Fig. 9a




Fig. 9b

10/13




Fig. 10




Fig. 11

12 / 13




Fig. 12




Fig. 13

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/41360

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 B29C45/76 B29C45/28 B29C45/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B29C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 052 078 A (HEKUMA HERBST MASCHINENBAU GMB) 15 November 2000 (2000-11-15)	1,2,8,9, 11-13, 16-21, 23,25, 26,28-31
A	column 20, line 7 -column 20, line 48 column 17, line 28 -column 17, line 35 -----	3,19
X	US 6 287 107 B1 (MOSS MARK D ET AL) 11 September 2001 (2001-09-11)	1,2,7-9, 11,12, 17,18, 20,21, 25-31
A	column 16, line 61 -column 17, line 10; figure 19 -----	4-6, 13-15, 22,23

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the International filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the International filing date but later than the priority date claimed

T later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the International search

16 April 2003

Date of mailing of the International search report

06/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3018

Authorized officer

Zattoni, F

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 02/41360

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1052078	A	15-11-2000	DE 19949850 A1	07-12-2000
			EP 1052078 A1	15-11-2000
			JP 2000343566 A	12-12-2000
US 6287107	B1	11-09-2001	US 6419870 B1	16-07-2002
			US 6294122 B1	25-09-2001
			US 6361300 B1	26-03-2002
			US 6062840 A	16-05-2000
			AU 1248801 A	06-06-2001
			EP 1242227 A2	25-09-2002
			WO 0134364 A2	17-05-2001
			US 2002164392 A1	07-11-2002
			US 2002121713 A1	05-09-2002
			US 2002132025 A1	19-09-2002
			US 6309208 B1	30-10-2001
			EP 0967063 A1	29-12-1999
			CA 2329706 A1	28-10-1999
			EP 1073551 A1	07-02-2001
			JP 2002513687 T	14-05-2002
			WO 9954109 A1	28-10-1999
			US 2003012845 A1	16-01-2003
			US 2002190413 A1	19-12-2002
			US 6464909 B1	15-10-2002
			US 6343921 B1	05-02-2002
			US 6343922 B1	05-02-2002
			US 6254377 B1	03-07-2001
			US 6436320 B1	20-08-2002
			US 6514440 B1	04-02-2003
			CA 2246771 A1	02-03-1999
			CA 2360509 A1	02-03-1999
			EP 0901896 A2	17-03-1999
			US 6261075 B1	17-07-2001

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.